



7300w² Monitor

THE 7300w² MONITOR IS DESIGNED TO OFFER MONITORING OF MULTIPLE PARAMETERS FROM A CENTRALIZED LOCATION. THIS FLEXIBLE ONLINE SYSTEM IS SUITABLE FOR USE ACROSS A FULL RANGE OF DRINKING WATER AND WASTEWATER APPLICATIONS.

INTEGRATED SOLUTION

- The 7300w² Monitor is part of a complete digital portfolio and can be used with the full line of turbidity, dissolved oxygen, multiparameter, and WaterTechw² sensors to log and display data and transmit it to a SCADA system.

FLEXIBLE CONTROL

- With Modbus or 4-20 mA connections, the system is easy to expand using the WaterWatch² Expansion Box if additional measurements are required.
- The monitor's smart design interfaces with individual sensors, allowing for connection of 2 inputs, up to 8 sensrs (with the Expansion Box) to measure up to 16 parameters.
- Expansion and junction boxes can be used to customize the monitoring system and to increase the distance between sensor installations.
- Built-in, user-configurable trending display shows the previous 24 hours of data for any measurement point on an easy-to-navigate graph that can be downloaded for reporting.

TOTAL FIELD SUPPORT

- Our team of experts provides outstanding customer service and technical support.

PARAMETERS

- TSS
- Turbidity
- Temperature
- pH & ORP
- DO
- Color
- Conductivity
- Ammonium
- Pressure
- Level
- Salinity
- Nitrate
- Chloride



BESTOBELL
AQUATRONIX

SINCE / DEPUIS 1953

BEP-Bestobell

www.bestobell.com

Applications:

- **DRINKING WATER AND WASTEWATER PROCESS MONITORING**

GENERAL		7300w ² Monitor	
DIMENSIONS	185mm (7.3") x 213mm (8.4") x 3.7 (3.7")	RELAYS	3 (reduced to 1 relay for Modbus/Profibus)
WEIGHT	1.4 kg (3.1lbs)	RELAY TYPE	SPCO
PROTECTION CLASS	IP65	RELAY RATING	Max 5A @30VDC/230VAC
ENCLOSURE MATERIAL	Polycarbonate (PC)	AUXILIARY CONNECTIONS	Configurable for Remote Input, Device Power
CABLE ENTRIES	1x M20, 4xM16, 1 x USB Type A	DIGITAL COMMUNICATIONS	ModTechw ² - RS485
OPERATING TEMPERATURE	-20 to +70 °C (-4 to 158 °F) 0-95% Humidity (Non-Condensing)	DISPLAY	Graphical LCD, Black on White
POWER SUPPLY	85 to 264 VAC 50/60 Hz or 9 to 36 VDC	BACKLIGHT	On/Off/On after keypress, with user adjustable contrast
POWER RATING	AC Supply - 0.8A or DC Supply - 30W PN 230043 can be offered with AC versions in order to maintain cMETus approval standards.	KEYPAD	6 Key
ANALOGUE OUTPUTS	0/4-20mA, max load 750 ohms	TRENDING DISPLAY	24 hour trend display - user configurable
SERIAL OUTPUTS	Modbus RTU/RS485 & Profibus DP (expansion box required for Profibus DP)	DATALOGGING	USB port for user memory stick 10,000 records limit User configurable intervals 1-999 seconds

GENERAL		WaterWatch ² Expansion Boxes	
expansion	typical use	input	output
WaterWatch ² Expansion Box (1 x 4-20mA Input)	Connection to any Partech/Chemscan Monitor	1 x 4-20mA Analog Input	Monitor Connection
WaterWatch ² Expansion Box (3 to 4 Sensor Input)	Partech/Chemscan Modbus Slave Monitor	3 to 4 Sensor Input	Monitor Connection
WaterWatch ² Expansion Box (3 to 4 Sensor Input, 4 x 4-20mA and 4 x Relay Outputs)	Connection to Partech/Chemscan 4-20mA output monitor	3 to 4 Sensor Input	Monitor Connection, 4 x 4-20mA and 4 x Relay Outputs
WaterWatch ² Expansion Box (3 to 8 Sensor Input)	Partech/Chemscan Modbus Slave Monitor	3 to 8 Sensor Input	Monitor Connection
WaterWatch ² Expansion Box (Profibus DP, via Interface Unit, Cable Length: 1 metre/3.2ft)	Partech/Chemscan Modbus Slave Monitor	Monitor Connection for Profibus	Profibus DP, via Interface Unit
Warranty - 2 years			

BESTOBELL
AQUATRONIX
SINCE/DEPUIS 1953

Head Office
2880 Argentinia Road, Unit 3
Mississauga, ON L5N 7X8
salesdesk@bestobell.com
1-800-668-3979
www.bestobell.com

Montréal Office
970 Montée de Liesse, #204
St.Laurent, QC H4T 1W7
ventes@bestobell.com
1-877-331-1225

Atlantic Office
166 North Side Road
Riverport, NS B0J 2W0
dmossman@bestobell.com
902-529-0355

Since 1953, Quality Products to Sense, Measure & Control
Depuis 1953, Produits De Qualités Pour Détecter, Mesurer & Contrôler

in-situ.com

132237DS-Iss18
Copyright © 2022 In-Situ Inc. All rights reserved. May 2022.

